






| Input & Output | EU | | UK |
|-------------------------------------|------------------------------|-------------------|----------------------------|
| Rated Input Voltage | AC 230V | AC 230V | AC 230V |
| Rated Input Frequency | 50/60Hz | 50/60Hz | 50/60Hz |
| Rated Output Voltage | AC 230V | AC 230V | AC 230V |
| Input plug | 1P+N+PE | 1P+N+PE | 1P+N+PE |
| Rated Output Frequency | 50/60Hz | 50/60Hz | 50/60Hz |
| Max. Output Current | 16A | 32A | 13A |
| Adjustable Current | 16A/13A/10A/8A | 32A/24A/16A/10A | 13A/10A/8A/6A |
| Max. Output Power | 3.6kW | 7.2kW | 3.0kW |
| Residual Current (TYPE A) | ● | ● | ● |
| Residual Current (TYPE A+DC 6mA) | ○ | ○ | ○ |
| User Interface & Control | | | |
| LCD | ○ | ○ | ○ |
| Touch buttons | ○ | ○ | ○ |
| Indicator Light | ● | ● | ● |
| WIFI & Bluetooth | ○ | ○ | ○ |
| APP | ○ | ○ | ○ |
| Working Environment | | | |
| Working temperature | -20°C/-30°C~+50°C | -20°C/-30°C~+50°C | -20°C/-30°C~+50°C |
| Storage temperature | -30°C/-40°C~+85°C | -30°C/-40°C~+85°C | -30°C/-40°C~+85°C |
| Altitude | ≤ 2000 m | ≤ 2000 m | ≤ 2000 m |
| Safety | | | |
| Size(L*W*H) | 138.1*66.1*30.3 | 138.1*66.1*30.3 | 138.1*66.1*30.3 |
| Over/Under Voltage | ● | ● | ● |
| Over current | ● | ● | ● |
| Over Temperature protection | ● | ● | ● |
| Ground Protection | ● | ● | ● |
| Leakage Protection | ● | ● | ● |
| Authentication | TUV CE CB Energy Star | | UKCA CB Energy Star |

- Standard features
- optional features
- not available





| Input & Output | JP | Au/Nz | SG |
|-------------------------------------|------------------------|---------------------------|-------------------|
| Rated Input Voltage | AC 110V/200V | AC 230V | AC 230V |
| Rated Input Frequency | 50Hz | 50Hz | 50Hz |
| Rated Output Voltage | AC 110V/220V | AC 230V | AC 230V |
| Input | L+N+PE | L+N+PE | L+N+PE |
| Rated Output Frequency | 50Hz | 50Hz | 50Hz |
| Max. Output Current | 15A | 32A | 32A |
| Adjustable Current | 15A/13A/10A/8A | 32A/24A/16A/10A | 32A/24A/16A/10A |
| Max. Output Power | 3kW | 7.2kW | 7.2kW |
| Residual Current (TYPE A) | ● | ● | ● |
| Residual Current (TYPE A+DC 6mA) | ○ | ○ | ○ |
| User Interface & Control | | | |
| LCD | ○ | ○ | ○ |
| Touch buttons | ○ | ○ | ○ |
| Indicator Light | ● | ● | ● |
| WIFI & Bluetooth | ○ | ○ | ○ |
| APP | ○ | ○ | ○ |
| Working Environment | | | |
| Working temperature | -20°C/-30°C~+50°C | -20°C/-30°C~+50°C | -20°C/-30°C~+50°C |
| Storage temperature | -30°C/-40°C~+85°C | -30°C/-40°C~+85°C | -30°C/-40°C~+85°C |
| Altitude | ≤ 2000 m | ≤ 2000 m | ≤ 2000 m |
| Safety | | | |
| Size(H*W*D) | 138.1*66.1*30.3 | 138.1*66.1*30.3 | 138.1*66.1*30.3 |
| Over/Under Voltage | ● | ● | ● |
| Over current | ● | ● | ● |
| Over Temperature protection | ● | ● | ● |
| Ground protection | ● | ● | ● |
| Leakage protection | ● | ● | ● |
| Authentication | PSE Energy Star | SAA CB Energy Star | TR25 CB |

● Standard features
 ○ optional features
 – not available




| Input & Output | NA | | |
|-------------------------------------|------------------------|-------------------|-------------------|
| | Rated Input Voltage | AC 120V/240V | AC 240V |
| Rated Input Frequency | 50/60Hz | 50/60Hz | 50/60Hz |
| Rated Output Voltage | AC 120V/240V | AC 240V | AC 240V |
| Input | L1+L2/N+PE | L1+L2+PE | L1+L2+PE |
| Rated Output Frequency | 50/60Hz | 50/60Hz | 50/60Hz |
| Max. Output Current | 16A | 32A | 40A |
| Adjustable Current | 16A/13A/10A/8A | 32A/24A/16A/10A | 40A/32A/24A/16A |
| Max. Output Power | 3.8kW | 7.6kW | 9.6kW |
| Residual Current Detection | Type A | Type A | Type A |
| User Interface & Control | | | |
| LCD | ○ | ○ | ○ |
| Touch buttons | ○ | ○ | ○ |
| Indicator Light | ● | ● | ● |
| WIFI & Bluetooth | ○ | ○ | ○ |
| APP | ○ | ○ | ○ |
| Working Environment | | | |
| Working temperature | -20°C/-30°C~+50°C | -20°C/-30°C~+50°C | -20°C/-30°C~+50°C |
| Storage temperature | -30°C/-40°C~+85°C | -30°C/-40°C~+85°C | -30°C/-40°C~+85°C |
| Altitude | ≤ 2000 m | ≤ 2000 m | ≤ 2000 m |
| Safety | | | |
| Size(H*W*D) | 138.1*66.1*30.3 | 138.1*66.1*30.3 | 138.1*66.1*30.3 |
| Over/Under Voltage | ● | ● | ● |
| Over current | ● | ● | ● |
| Over Temperature protection | ● | ● | ● |
| Ground protection | ● | ● | ● |
| Leakage protection | ● | ● | ● |
| Authentication | UL ETL FCC Energy Star | | |

- Standard features
- optional features
- not available





● Standard features
○ optional features
– not available

| Input & Output | EU | | |
|-------------------------------------|---------------------|-------------------|-------------------|
| | Rated Input Voltage | AC 230V | AC 400V |
| Rated Input Frequency | 50/60Hz | 50/60Hz | 50/60Hz |
| Rated Output Voltage | AC 230V | AC 400V | AC 400V |
| Input | 1P+N+PE | 3P+N+PE | 3P+N+PE |
| Rated Output Frequency | 50/60Hz | 50/60Hz | 50/60Hz |
| Max. Output Current | 32A | 16A | 32A |
| Adjustable Current | 32A/24A/16A/10A | 16A/13A/10A/8A | 32A/24A/16A/10A |
| Max. Output Power | 7kW | 11kW | 22kW |
| Residual Current (TYPE A) | ● | ● | ● |
| Residual Current (TYPE A+DC 6mA) | ○ | ○ | ○ |
| User Interface & Control | | | |
| LCD | ○ | ○ | ○ |
| Indicator Light | ○ | ○ | ○ |
| RFID | ○ | ○ | ○ |
| WIFI & Bluetooth | ○ | ○ | ○ |
| APP | ○ | ○ | ○ |
| Serial Communication | ○ | ○ | ○ |
| Ethernet | ○ | ○ | ○ |
| 4G | ○ | ○ | ○ |
| OCPP | ○ | ○ | ○ |
| MUDBUS | ○ | ○ | ○ |
| Working Environment | | | |
| Working temperature | -20°C/-30°C~+50°C | -20°C/-30°C~+50°C | -20°C/-30°C~+50°C |
| Storage temperature | -30°C/-40°C~+85°C | -30°C/-40°C~+85°C | -30°C/-40°C~+85°C |
| Altitude | ≤ 2000 m | ≤ 2000 m | ≤ 2000 m |
| Safety | | | |
| Size(L*W*H) | 210*110*31.3 | 210*110*31.3 | 210*110*31.3 |
| Over/Under Voltage | ● | ● | ● |
| Over current | ● | ● | ● |
| Over Temperature protection | ● | ● | ● |
| Ground protection | ● | ● | ● |
| Leakage protection | ● | ● | ● |
| Authentication | | | |
| TUV CE CB Energy Star | | | |



● Standard features
○ optional features
– not available

| Input & Output | NA |
|-----------------------------|------------------------|
| Rated Input Voltage | AC 240V |
| Rated Input Frequency | 50/60Hz |
| Rated Output Voltage | AC 240V |
| Input | L1+L2+PE |
| Rated Output Frequency | 50/60Hz |
| Max. Output Current | 48A |
| Adjustable Current | 48A/40A/32A/24A/16A |
| Max. Output Power | 11.5kW |
| Residual Current Detection | Type A |
| Communication & Protocol | |
| LCD | ○ |
| Indicator Light | ○ |
| RFID | ○ |
| WIFI & Bluetooth | ○ |
| APP | ○ |
| Serial Communication | ○ |
| Ethernet | ○ |
| 4G | ○ |
| OCPP | ○ |
| MODUBUS | ○ |
| Working Environment | |
| Working temperature | -20°C/-30°C~+50°C |
| Storage temperature | -30°C/-40°C~+85°C |
| Altitude | ≤ 2000 m |
| Safety | |
| Size(L*W*H) | 209.7*109.7*44.2 |
| Over/Under Voltage | ● |
| Over current | ● |
| Over Temperature protection | ● |
| Ground protection | ● |
| Leakage protection | ● |
| Authentication | |
| | UL ETL FCC Energy Star |




● Standard features
○ optional features
– not available

| Input & Output | EU | |
|-------------------------------------|-----------------------|-------------------|
| Rated Input Voltage | AC 400V | AC 400V |
| Rated Input Frequency | 50/60Hz | 50/60Hz |
| Rated Output Voltage | AC 400V | AC 400V |
| Input | 3P+N+PE | 3P+N+PE |
| Rated Output Frequency | 50/60Hz | 50/60Hz |
| Max. Output Current | 16A | 32A |
| Adjustable Current | 16A/13A/10A/8A | 32A/24A/16A/10A |
| Max. Output Power | 11kW | 22kW |
| Residual Current (TYPE A) | ● | ● |
| Residual Current (TYPE A+DC 6mA) | ○ | ○ |
| User Interface & Control | | |
| LCD | ● | ● |
| Indicator Light | ● | ● |
| RFID | – | – |
| WIFI & Bluetooth | ○ | ○ |
| APP | ○ | ○ |
| Serial Communication | – | – |
| Ethernet | – | – |
| 4G | – | – |
| OCPP | – | – |
| MUDBUS | – | – |
| Working Environment | | |
| Working temperature | -20°C/-30°C~+50°C | -20°C/-30°C~+50°C |
| Storage temperature | -30°C/-40°C~+85°C | -30°C/-40°C~+85°C |
| Altitude | ≤ 2000 m | ≤ 2000 m |
| Safety | | |
| Size(L*W*H) | 173.1*89.1*32.2 | 173.1*89.1*32.2 |
| Over/Under Voltage | ● | ● |
| Over current | ● | ● |
| Over Temperature protection | ● | ● |
| Ground protection | ● | ● |
| Leakage protection | ● | ● |
| Authentication | TUV CE CB Energy Star | |



Fully functional automatic testing equipment

| | |
|--|---|
| Insulation Testing | ● |
| Voltage Withstand Testing | ● |
| Conduction Testing | ● |
| CP Voltage Testing | ● |
| CP Frequency Testing | ● |
| Duty Cycle Testing | ● |
| Grounding Protection Testing | ● |
| Residual Current Protection Testing(AC+DC) | ● |
| Residual Current Protection Testing(CCID 20) | ● |
| Overcurrent Protection Testing | ● |
| Overvoltage Protection Testing | ● |
| Undervoltage Protection Testing | ● |
| Bluetooth WIFI Matching Testing | ● |



● Standard features
○ optional features
– not available